



SETRAL® – NEW LUBRICANT LINE WITH ADVANCED BASE OIL TECHNOLOGY

New member – setral® adds a new base oil to the portfolio

Features:

- ✓ Innovative base oil technology
- ✓ Exceptional oxidation stability compared to standard base oils
- ✓ Excellent low- and high-temperature properties
- ✓ Good material compatibility
- ✓ Free from PFAS, TPPT and silicone oil

Benefits:

- ✓ Extended lubricant lifetime
- ✓ Reduced maintenance and relubrication intervals
- ✓ Wide operating temperature range
- ✓ Suitable for a wide range of applications
- ✓ Aligned with evolving regulatory requirements

setral® – Competence in Lubricants

As always, setral® continues to search for innovative solutions and new products, constantly evaluating options for future-oriented lubricant formulations. This includes the assessment of potential raw materials, such as base oils, and the development of new products based on promising candidates.



setral®

Competence in Lubricants

setral[®] lubricants based on an innovative base oil technology

For more information about individual products, technical or safety data sheets, please visit our website or contact our experts: info@setral.net




Features and benefits:

- Base oil shows up to 4 times higher oxidation stability vs. PAO in laboratory tests
- Good wear properties
- Excellent corrosion protection characteristics
- Free of typical paint wetting impairment substances (PWIS), e.g. silicone oil, PTFE, PFPE

Suitable for many industries

✓ Especially (but not exclusively) for:



New Greases

Special greases with an innovative formulation especially developed for long-term applications

PRODUCT	APPLICATION	BASE OIL	V40* [mm ² /s]	THICKENER	NLGI	TEMPERATURE RANGE [°C]
SYN-setral-LI/C 2-100 NT	For various metal/metal, metal/plastic friction pairings, e.g.: • Loaded roller bearings • Plain bearings • Power windows, sunroofs, sun visors • Seat adjusters, steering column adjusters • Armrests and mirrors adjusters • Cup holders, horn contacts • Bowden cables • HVAC system controllers • Small gears	Synthetic	100	Lithium complex	2	-40 - +160 (short +180)
SYN-setral-SD 2-100 NT	For various metal/metal, metal/plastic friction pairings, e.g.: • Sliding surfaces, guide rails or rods • Lifting cylinders • Armatures, tap cocks, joints • Clutch release bearings • Household appliances and fans • Electric motors and electrical contacts • Bearings and gears	Synthetic	100	Inorganic	2	-40 - +200 (short +215)

*V40 = base oil viscosity at 40 °C



New oils

Fully synthetic oils with innovative formulation

PRODUCT	APPLICATION	BASE OIL	VISCOSITY AT 40 °C [mm ² /s]	TEMPERATURE RANGE [°C]
FLUID-setral-NT 100	• Versatile lubricating oil • Assembly oil e.g., for O-ring assembly • Release agent without silicone oil • Noise reduction, e.g. squeak and rattle	Synthetic	95	-40 - +160 (short +180)
FLUID-setral-NT 32 (Spray)	• Silicone-free release agent suitable for a wide temperature range • Versatile lubricating oil • Noise reduction, e.g. squeak and rattle	Synthetic	36	-40 - +190



Setral Chemie GmbH
Salzsteinstrasse 4
D-82402 Seeshaupt
Tel. +49 (0) 88 01 / 97 10
Fax +49 (0) 88 01 / 97 30
info@setral.net

Sétral S.à.r.l.
13, rue Tannmühle
F-67310 Romanswiller
Tel. +33 (0) 3 88 / 59 11 59
Fax +33 (0) 3 88 / 59 11 57
france@setral.net

Version: September 2026



www.setral.net